

202/05



Made with EN AW-5754 UNI EN 573-3 light alloy plate, 1,5 mm thick, anodised after finishing. The upper rim is reinforced through a light alloy section.

A light alloy section runs all along the lower rim. The movable tray is controlled through one galvanised steel large spring; the tray is kept horizontal through a galvanised steel pantograph.

Spring capacity: Kg 70

Mounted on 4 rubber wheels diam.160 mm (two fix and two swivel) arrangement longwise.

Weight: 20kg



Inner dimensions:

Length: 1470 mm
Deepness: 900 mm
Highness: 520 mm

Outer dimensions:

Length: 1520 mm
Deepness: 950 mm
Highness: 840 mm

TECHINICAL DATASHEET 202/05

Shelfspan

making better use of space

 **conf**
industries

Rev.1 – 03/05/21

Optional:

- **TSA**
Upperintegratedantimark bumperinPVC



202/10



Made with EN AW-5754 UNI EN 573-3 light alloy plate, 1.5 mm thick, anodised after finishing. The upper rim is reinforced through a light alloy section.

A light alloy section runs all along the lower rim. The movable tray is controlled through one galvanised steel large spring; the tray is kept horizontal through a galvanised steel pantograph.

Spring capacity: Kg 65

Mounted on 4 rubber wheels diam. 125 mm (two fix and two swivel) arrangement longwise.

Weight: 20 kg



Inner dimensions:

Length: 1400 mm
Depth: 700 mm
Height: 520 mm

Outer dimensions:

Length: 1450 mm
Depth: 750 mm
Height: 800 mm

Optional:

- TSA
Upper integrated anti-mark bumper in PVC



202/30



Made with EN AW-5754 UNI EN 573-3 light alloy plate, 1.5 mm thick, anodised after finishing. The upper rim is reinforced through a light alloy section.

A light alloy section runs all along the lower rim. The movable tray is controlled through one galvanised steel large spring; the tray is kept horizontal through a galvanised steel pantograph.

Spring capacity: Kg 55

Mounted on 4 rubber wheels diam. 125 mm (all swivel) arrangement at the corners.



Inner dimensions:

Length: 1250 mm
Deepness: 650 mm
Highness: 520 mm

Outer dimensions:

Length: 1300 mm
Deepness: 700 mm
Highness: 800 mm

Optional:

- **TSA**
Upper integrated antimark bumper in PVC



202/50



Made with EN AW-5754 UNI EN 573-3 light alloy plate, 1,5mm thick, anodised after finishing. The upper rim is reinforced through a light alloy section.

A light alloy section runs all along the lower rim. The movable tray is controlled through one galvanised steel large spring; the tray is kept horizontal through a galvanised steel pantograph.

Spring capacity: Kg 45

Volume 340 lt.

Mounted on 4 rubber wheels diam. 125 mm (all swivel) arrangement at the corners.



Inner dimensions:

Length: 1000 mm
Deepness: 600 mm
Highness: 520 mm

Outer dimensions:

Length: 1050 mm
Deepness: 650 mm
Highness: 800 mm

Optional:

- TSA
Upper integrated anti-mark bumper in PVC



202/60



Made with EN AW-5754 UNI EN 573-3 light alloy plate, 1,5mm thick, anodised after finishing. The upper rim is reinforced through a light alloy section.

A light alloy section runs all along the lower rim.

The movable tray is controlled through one galvanised steel large spring; the tray is kept horizontal through a galvanised steel pantograph.

Spring capacity: Kg 30

Mounted on 4 rubber wheels diam. 125 mm (all swivel) arrangement at the corners.



Inner dimensions:

Length: 920 mm

Depth: 600 mm

Height: 520 mm

Outer dimensions:

Length: 970 mm

Depth: 650 mm

Height: 800 mm

Optional:

- **TSA**
Upper integrated anti-mark bumper in PVC



202/70



Made with EN AW-5754 UNI EN 573-3 light alloy plate, 1,5mm thick, anodised after finishing. The upper rim is reinforced through a light alloy section.

A light alloy section runs all along the lower rim.

The movable tray is controlled through one galvanised steel large spring; the tray is kept horizontal through a galvanised steel pantograph.

Spring capacity: Kg 30

Mounted on 4 rubber wheels diam. 125 mm (all swivel) arrangement at the corners.

Inner dimensions:

Length: 1040 mm
Depth: 400 mm
Height: 520 mm

Outer dimensions:

Length: 1090 mm
Depth: 450 mm
Height: 800 mm

Optional:

- TSA
Upper integrated anti-mark bumper in PVC

